AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application. Where claims have been amended and/or canceled, such amendments and/or cancellations are done without prejudice and/or waiver and/or disclaimer to the claimed and/or disclosed subject matter, and Applicants reserve the right to claim this subject matter and/or other disclosed subject matter in a continuing application or otherwise.

- 1. (currently amended) A pathway determination system for a data storage system comprising having N storage devices and more than N pathways for retrieving requested data from the data storage system, the pathway determination system comprising:
- a sorter <u>capable of</u> receiving a read request and separating the read request into an appropriate segment size for sending to the storage devices of the data storage system;
- an assigner <u>capable of</u> selecting a read permutation satisfying the received read request, the selected read permutation being based <u>at least in part</u> on a predetermined metric, and the assigner <u>being capable of</u> sending the selected read permutation to the storage devices of the storage system; and
- a collector <u>capable of receiving</u> the requested data from the N storage devices in response to the selected read permutation being sent to the storage devices.
- 2. (currently amended) The system according to claim 1, wherein the assigner <u>is</u> further <u>capable of generatinggenerates</u> the read permutations satisfying the received read request.
- 3. (currently amended) The system according to claim 2, wherein <u>the assigner</u> generates the read permutations are generated before the read request is received.
- 4. (currently amended) The system according to claim 1, wherein the assigner comprises includes:
- a permutation generator <u>capable of generating</u> the read permutations; and a cost calculator <u>capable of calculating</u> an expense of each permutation based on the predetermined metric.

- 5. (currently amended) The system according to claim 4, wherein the cost calculator is capable of utilizing utilizes queue length information and estimated current cost information, and
- wherein the permutation generator <u>is capable of generatinggenerates</u> a reduced number of read permutations based <u>at least in part</u> on the queue length information and the estimated current cost information.
- 6. (currently amended) The system according to claim 5, wherein the cost calculator is capable of calculating calculates the expense of each permutation further based at least in part on performance information received from the storage devices of the storage system.
- 7. (currently amended) The system according to claim 1, wherein the storage system comprises includes at least one failed storage device.
- 8. (currently amended) The system according to claim 1, wherein the metric is dynamically changed based <u>at least in part</u> on a change in operating conditions of the storage system.
- 9. (currently amended) The system according to claim 8, wherein the metric is periodically changed based <u>at least in part on operating conditions of the storage system.</u>
- 10. (currently amended) The system according to claim 1, wherein the metric is based at least in part on a current workload balance for the storage devices of the data system.
- 11. (currently amended) The system according to claim 1, wherein the metric is based <u>at least in part</u> on an estimated delay before the requested data can be retrieved from the storage devices of the storage system.
- 12. (currently amended) The system according to claim 1, wherein the metric is based at least in part on a number of outstanding requests in the queue of a storage device of the storage system.

- 13. (currently amended) The system according to claim 1, wherein the metric is based at least in part on a total queue for all outstanding requests that have been received by the storage system.
- 14. (currently amended) A method for determining a pathway for obtaining data stored in a data storage system <u>comprisinghaving</u> N storage devices and more than N pathways for retrieving requested data from the data storage system, the method comprising steps of:

receiving a read request from a requester;

separating the read request into an appropriate segment and size for sending the storage devices of the data storage system;

selecting a read permutation from possible read permutations satisfying the received read request;

sending the selected read permutation to the storage devices of the storage system; receiving the requested data from the N storage devices in response to the selected read permutation being sent to the storage devices; and

returning the satisfied read request to the requester.

- 15. (currently amended) The method according to claim 14, further comprising a step of generating the read permutations satisfying the received read request.
- 16. (currently amended) The method according to claim 15, wherein the step of generating the read permutations is performed before the read request is received.
- 17. (currently amended) The method according to claim 15, further comprising a step of calculating an expense of each permutation based at least in part on the predetermined metric.
- 18. (currently amended) The method according to claim 17, further comprising steps of:

generating queue length information and estimated current cost information, and generating a reduced number of read permutations based at least in part on the

queue length information and the estimated current cost information.

- 19. (currently amended) The method according to claim 18, wherein the step of calculating the expense of each permutation is further based at least in part on performance information received from the storage devices of the storage system.
- 20. (currently amended) The method according to claim 14, wherein the storage system <u>comprisesineludes</u> at least one failed storage device.
- 21. (currently amended) The method according to claim 14, further comprising a step of dynamically changing the metric based at least in part on a change in operating conditions of the storage system.
- 22. (currently amended) The method according to claim 14, further comprising a step of periodically changing the metric based at least in part on operating conditions of the storage system.
- 23. (currently amended) The method according to claim 14, wherein the metric is based at least in part on a current workload balance for the storage devices of the data system.
- 24. (currently amended) The method according to claim 14, wherein the metric is based <u>at least in part</u> on an estimated delay before the requested data can be retrieved from the storage devices of the storage system.
- 25. (currently amended) The method according to claim 14, wherein the metric is based at least in part on a number of outstanding requests in the queue of a storage device of the storage system.
- 26. (currently amended) The method according to claim 14, wherein the metric is based at least in part on a total queue for all outstanding requests that have been received by the storage system.